

BIOVAST TRELLEBORG RUBBER HOSE

HOSES › Hot water hoses

Food grade NBR compound rubber hose



- Eu regulations guide n° 1935/2004,2023/2006
- American FDA directive n° 21 CFR 177.2600
- German directive Bfr, Empfehlung XXI, Category 3
- French institute of poiters (IANESCO)



Mastertubi.it?q?357

NBR tube, smooth white suitable for the transfer of aqueous fluids, acids, edible alcohol (up to 70°C), fatty food products. Highly resistant textile inserts. Smooth, scratch- and stain-resistant blue cover, resistant to hydrocarbons, animal and vegetable fats.

Applications:

cleaning with steam up to 165°C and hot water in the food industry, circulation of hot liquids: Water up to +100° at 20 bar, steam up to +165° at 6 bar.

Fatty food products.

Burst pressure 3 times the operating pressure.

OPERATING TEMPERATURE: -20° +165° C

Code	Diameters mm	radius curvature mm	Weight g/m	Rolls m
09GBIOVAST13/23	13x23	65	380	20-40-80
09GBIOVAST16/26	16x26	85	440	20-40-80
09GBIOVAST19/31	19x31	100	630	20-40-80
09GBIOVAST25/37	25x37	125	780	20-40