

STARKLER TUBE - HEAT 20

HOSES › Hot water hoses

Applications

Versatile hose for high pressure cleaning and service operations
general drain for supplying hot or cold water and many other fluids
(see chemical resistance table for EPDM).

Suitable for all sectors: construction and public works, industry, agriculture.

Advantages

Extremely resistant to aging and atmospheric conditions.

Wide operating temperature range (-30°C to +100°C).

Wide range of diameters. Excellent mechanical properties. Resistant to many fluids.

Long lasting heavy duty hose.

EPDM tube, smooth, black

Synthetic fabric reinforcement

EPDM cover, smooth for internal diameters from 12.7 to 25.4 mm,


knurled for internal diameters from 30 to 38 mm

Black color with orange longitudinal stripes

Operating temperature range: -30° to +100° C.

Standard tolerances compliant with ISO 1403 type 2 (except marking)

standard packs of: 20 - 40 - 80 metres



Mastertubi.it/q?9

diameter internal mm	thickness wall mm	diameter external mm	Pressure of exercise Cafe	Burst pressure Cafe	radius Of curvature mm	weight Kg/m
12.7	4.0	20.7	20	60	55	0.27
15.8	4.1	24.0	20	60	70	0.33
19.4	4.5	28.4	20	60	85	0.43
25.4	4.8	35.0	20	60	100	0.58
30.0	4.25	39.0	10	30	240	0.72
32.0	4.25	41.0	10	30	260	0.77
35.0	4.25	44.0	10	30	280	0.83
38.0	4.25	47.0	10	30	310	0.89