


RIBBED ASPIROIL/10 HOSE

HOSES › Specific flexible hoses for engine test rooms

Hose for suction and delivery of fuels, oils and lubricants, diesel with aromatic content up to 50%. Smooth black NBR rubber tube, with textile reinforcement, steel spiral and incorporated copper cables for earthing.

Designed to give maximum comfort of use for operators, thanks to its qualities of extreme flexibility and easy handling.



Mastertubi.it/q?1162

Black cover, corrugated with canvas impression.

Antistatic rubber SBR/NBR/PVC resistant to abrasion, hydrocarbons, atmospheric agents and ozone.

Operating temperature: -30° +80° C

40 meter rolls

Operating pressure 10 bar, burst pressure 30 bar

Maximum depression value 0.9 bar

Code item	Dimension OR mm	radius Of curvature mm
06GBAS0000019GT	19x28	70
06GBAS0000025GT	25x34	85
06GBAS0000030GT	30x40	100
06GBAS0500032GT	32x42	105
06GBAS0000038GT	38x48	130
06GBAS0000040GT	40x50	135
06GBAS0000045 T	45x55	150
06GBAS0000051GT	50x61	165

06GBAS0000060GT	60x70	200
06GBAS0000063GT	63.5x73.5	220
06GBAS0000070GT	70x82	240
06GBAS0000076GT	76x90	250
06GBAS0000080GT	80x94	250
06GBAS0000090GT	90x105	270
06GBAS0000102GT	102x116	390