

## COPPER-PLATED POLYURETHANE HOSE (PUR-PHT) - 1.0

HOSES › Specific flexible hoses for engine test rooms

High performance hose for hot and abrasive powder, bulk material, granules and hot gases Blown film, cooling air on the extrusion tool offset printing machine, air supply cabinet Cooling air, UV dryer, IR/infrared dryer, textile industry, steam extraction, iron. Highly abrasion resistant excellent heat resistance

(better than comparable TPE and neoprene) good resistance to chemicals, industrial oils and hydrocarbons excellent cold flexibility.

RoHS REACH compliant based on technical information.

Temperature range: -40°C to 125°C briefly up to 150°C

Construction Pipe with profile reinforced with harmonic steel wire incorporated into the wall.

Wall in special patented high temperature polyurethane.

**Wall thickness approx. 1.0 mm**

Further sizes and lengths available upon request

**Standard color black**

**Standard packs 10 meters**



Mastertubi.it/q?1559

diameter internal	external diameter	Pressure	Depression	Radius of curvature	weight
mm	mm	bar	bar	mm	Kg/m
25	32	2,835	0.495	28	0.20
32	40	2,245	0.460	35	0.28
38	46	1,905	0.430	40	0.32
40	48	1,815	0.420	41	0.34
45	53	1,620	0.385	45	0.38
50	58	1,465	0.365	49	0.41
60	68	1,225	0.285	56	0.49
63	73	1,135	0.255	60	0.53
70	79	1,055	0.210	65	0.59
75	84	0.985	0.195	69	0.64

80	89	0.925	0.175	73	0.68
90	99	0.825	0.155	80	0.75
100	109	0.745	0.120	88	0.97
125	134	0,600	0.085	107	1.20
150	159	0.500	0.075	126	1.52
160	169	0.470	0.065	134	1.61
200	209	0.375	0.055	165	2.00