

TERM/K 90 TUBE - HEAT RESISTANT

HOSES › Specific flexible hoses for engine test rooms

Pipe for industrial and civil air conditioning systems.

Flexible hose made of a polyester fabric coated with special PVC reinforced by a harmonic steel spiral incorporated between two heat-sealed layers of fabric

Very flexible and light, exceptional axial compressibility.

Self-extinguishing, class M1 NF P92 503 standards

Operating temperature: -20° +90° C (peaks of 110°).

Bending radius: 0.7 x diameter.

Color: Grey.



Mastertubi.it/q?359

Also available in insulated or fibreglass version on request

Standard lengths: 12 meters

item	Dimensions Ø mm	Radius of curvature m	Pressure of bar exercise	Vacuum packed bar
11PVTEK000040 3	40	28	0.6	0.10
11PVTEK000051 3	51	36	0.6	0.1
11PVTEK000063 3	63	42	0.6	0.1
11PVTEK000070 3	70	49	0.5	0.08
11PVTEK000076 3	76	53	0.4	0.07
11PVTEK000082 3	82	56	0.4	0.07
11PVTEK000089 3	89	65	0.3	0.06
11PVTEK000102 3	102	70	0.3	0.06
11PVTEK000114 3	114	80	0.2	0.06
11PVTEK000121 3	121	88	0.20	0.06
11PVTEK000127 3	127	89	0.15	0.04
11PVTEK000133 3	133	93	0.15	0.04
11PVTEK000140 3	140	98	0.15	0.04

11PVTEK000152 3	152	51	105	325
11PVTEK000165 3	165	116	0.15	0.03
11PVTEK000178 3	180	123	0.15	0.03
11PVTEK000203 3	200	140	0.15	0.03
11PVTEK000228 3	228	160	0.07	0.03
11PVTEK000254 3	254	175	0.07	0.03
11PVTEK000279 3	279	195	0.05	0.02
11PVTEK000304 3	304	210	0.05	0.02
11PVTEK000330 3	330	220	0.04	0.01
11PVTEK000355 3	356	235	0.04	0.01
11PVTEP000406 3	406	280	0.03	0.01
11PVTEP000457 3	457	320	0.02	0.01
11PVTEK000508 3	508	356	0.02	0.01
11PVTEK000558 3	558	390	0.02	0.01
11PVTEK000610 3	610	427	0.01	0.01