

AIR PIPE

HOSES › Specific flexible hoses for engine test rooms

AIR hose in plasticized PVC, with shock-proof PVC reinforcement spiral, very light and very flexible.

Use:

air intake and delivery, cold fumes, chemical gases, including aggressive ones, fine non-corrosive dust, wood chips, fine sawdust, air conditioning, generic industrial systems.



Mastertubi.it/q?382

Self-extinguishing according to UL 94 V0.

Smooth interior, corrugated exterior.

Radius of curvature equal to the internal diameter.

Operating temperature: -15°C to +60°C.

Colour: industrial grey, other colors on request.

| Code | Diameter mm | Weight g/m | Vacuum packed Cafe | Roll m |
|-----------------|-------------|------------|--------------------|--------|
| 11PVAIR000020 | 20 | 100 | 0.78 | 50 |
| 11PVAIR000025 | 25 | 140 | 0.44 | 50 |
| 11PVAIR000030 | 30 | 200 | 0.44 | 50 |
| 11PVAIR000032 | 32 | 215 | 0.44 | 50 |
| 11PVAIR000035 | 35 | 240 | 0.44 | 50 |
| 11PVAIR000038 | 38 | 265 | 0.44 | 50 |
| 11PVAIR000040 3 | 40 | 280 | 0.44 | 50 |
| 11PVAIR000045 | 45 | 360 | 0.44 | 50 |
| 11PVAIR000050 3 | 50 | 450 | 0.39 | 50 |
| 11PVAIR000060 3 | 60 | 540 | 0.39 | 50 |
| 11PVAIR000063 | 63 | 565 | 0.34 | 50 |
| | | | | |

| | | | | |
|-----------------|-----|------|------|----|
| 11PVAIR000065 | 65 | 590 | 0.34 | 50 |
| 11PVAIR000070 3 | 70 | 640 | 0.34 | 50 |
| 11PVAIR000075 | 75 | 690 | 0.34 | 50 |
| 11PVAIR000080 3 | 80 | 780 | 0.34 | 30 |
| 11PVAIR000090 3 | 90 | 830 | 0.34 | 30 |
| 11PVAIR000100 3 | 100 | 980 | 0.34 | 30 |
| 11PVAIR000110 | 110 | 1100 | 0.29 | 30 |
| 11PVAIR000120 3 | 120 | 1200 | 0.29 | 30 |
| 11PVAIR000125 | 125 | 1250 | 0.29 | 30 |
| 11PVAIR000130 3 | 130 | 1300 | 0.29 | 30 |
| 11PVAIR000140 3 | 140 | 1500 | 0.29 | 30 |
| 11PVAIR000150 3 | 150 | 1700 | 0.25 | 20 |
| 11PVAIR000160 3 | 160 | 1900 | 0.25 | 20 |
| 11PVAIR000170 | 170 | 2050 | 0.25 | 20 |
| 11PVAIR000180 3 | 180 | 2200 | 0.25 | 20 |
| 11PVAIR000200 3 | 200 | 2400 | 0.25 | 20 |
| 11PVAIR000250 | 250 | 3350 | 0.25 | 10 |
| 11PVAIR000300 3 | 300 | 4100 | 0.25 | 10 |