

## SILICONE SLEEVE (90 curve) HT/NMX 250 C red

HOSES › Specific flexible hoses for engine test rooms

### APPLICATION:

sleeves usable in air conditioning systems of civil and industrial vehicles, cogeneration units, marine engines, high temperature fluid transport.

### CHARACTERISTICS:

smooth in appearance externally and internally, not corruptible by antifreeze liquids or rust.  
 Excellent resistance to pressure, thermal aging and oxidizing agents (oxygen, ozone and UV rays)  
 Resistant to hardening the tube is resistant to compressive forces.  
 Ideal for use at high **temperatures between -60° and 250°C, it can reach temperatures up to 275°C for short periods of time** .

### CONSTRUCTION:

construction material silicone rubber VMQ (Vinyl-methyl HT) compliant with EU directive 2002/95/ECC for the restriction of the use of hazardous substances (RoHS). Structure reinforced with triple layer of ARAMID fiber fabric, contoured shape 90° curves. BRICK RED COLOR. Wall thickness 3.70 mm - tolerance +1/-0.5mm.

### LIMITATIONS:

compliance with the declared values, not suitable for the continuous passage and storage of hydrocarbons (even if resistant to traces of oil and diesel). It is not suitable for use at high vacuum, nor for the transport of abrasive powders.

ITEM	DESCRIPTION
10SILI250NOMEX90_032	SILICONE SLEEVE HT/NMX 250°C red - 90° CURVED - 150 STEM - 3 plies Ø 32
10SILI250NOMEX90_035	SILICONE SLEEVE HT/NMX 250°C red - 90° CURVED - 150 STEM - 3 plies Ø 35
10SILI250NOMEX90_040	SILICONE SLEEVE HT/NMX 250°C red - 90° CURVED - 150 STEM - 3 plies Ø 40
10SILI250NOMEX90_045	SILICONE SLEEVE HT/NMX 250°C red - 90° CURVED - 150 STEM - 3 plies Ø 45
10SILI250NOMEX90_050	SILICONE SLEEVE HT/NMX 250°C red - 90° CURVED - 150 STEM - 3 plies Ø 50
10SILI250NOMEX90_055	SILICONE SLEEVE HT/NMX 250°C red - 90° CURVED - 150 STEM - 3 plies Ø 55
10SILI250NOMEX90_060	SILICONE SLEEVE HT/NMX 250°C red - 90° CURVED - 150 STEM - 3 plies Ø 60
10SILI250NOMEX90_065	SILICONE SLEEVE HT/NMX 250°C red - 90° CURVED - 150 STEM - 3 plies Ø 65
10SILI250NOMEX90_070	SILICONE SLEEVE HT/NMX 250°C red - 90° CURVED - 150 STEM - 3 plies Ø 70
10SILI250NOMEX90_076	SILICONE SLEEVE HT/NMX 250°C red - 90° CURVED - 150 STEM - 3 plies Ø 76
10SILI250NOMEX90_080	SILICONE SLEEVE HT/NMX 250°C red - 90° CURVED - 150 STEM - 3 plies Ø 80
10SILI250NOMEX90_088	SILICONE SLEEVE HT/NMX 250°C red - 90° CURVED - 150 STEM - 3 plies Ø 88
10SILI250NOMEX90_090	SILICONE SLEEVE HT/NMX 250°C red - 90° CURVED - 150 STEM - 3 Ø 90 plies
	SILICONE SLEEVE HT/NMX 250°C red - 90° CURVED - 150 STEM - 3 plies

