

## CONDUCTIVE SOLVYKLER HOSE

HOSES › Chemical hoses

Flexible EPDM rubber hose for the industrial maintenance, chemical and painting sectors in service lines used for the passage of liquid solvents such as esters and ketones, alcohol-based paints, lacquers and for its work performance with chemical products in general. Excellent resistance to aging and atmospheric conditions, light and very flexible.

### Smooth antistatic black tube $R < 10^6 \text{ O/m}$ in EPDM

Textile braid inserted as reinforcement

Operating temperature  $-30^\circ +100^\circ\text{C}$

Green EPDM cover, coating resistant to paint splashes, solvents and aggressive chemicals. Does not contain silicone. 40 meter rolls.



Mastertubi.it/q?441

Code item	Dimensions Ø mm	radius of curvature mm	Weight g/m
10SOLVYKLE06/13	6x13	60	0.13
10SOLVYKLE09/16	9x16	85	0.17
10SOLVYKLE08/15	8x15	70	0.16
10SOLVYKLE10/18	10x18	90	0.22
10SOLVYKLE13/21	13x21	110	0.27
10SOLVYKLE16/24	16x24	130	0.32
10SOLVYKLE20/29	20x29	150	0.44
10SOLVYKLE25/34	25x34	170	0.54