

PETROVAST ANTISTATIC STEAM HOSE

HOSES › Steam hoses

Applications

For heavy industrial cleaning and the circulation of saturated and superheated steam in heating systems. Used in the petrochemical, construction, shipbuilding and chemical industries.

Advantages

Multipurpose hose. Highly flexible. High temperature resistance. Resistant to chemicals. Durable and safe performance. Meets international standards.

Tube: EPDM, smooth, black

Reinforcement: Brass coated steel, braided,

Cover: EPDM, fabric imprint, black,

Maximum operating pressure:

Water from -40° to +120°C 60 bar

Saturated steam +210°C 18

Superheated steam +230°C 18 bar

Burst pressure 180 bar

Electrical properties: conductive tube and cover, R <10⁶ Ω/m

Standard Tolerances / Approval ISO 6134: 2017 type 2 class A.

standard packs of: 20 - 40 - 60 metres

diameter internal mm	thickness wall mm	diameter external mm	radius of curvature mm	weight Kg/m
9.5	6	21.5	120	0.41
13.0	6	25.0	130	0.48
16.0	7	30.0	160	0.67
19.0	7	33.0	190	0.77
25.0	7.5	40.0	250	1.06
32.0	8	48.0	320	1.38
38.0	8	54.0	380	1.60
51.0	9	69.0	500	2.40